

UL Style 1061

HOOK UP WIRE



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including (UL) and CSA.

Part Number	AWG	Conductor		Nominal O.D. (inch)	Weight, Lbs. / 1000 ft.
		Strand	Type		
A6124-1T	24	SOLID	TC	.040	1.76
A6124-1	24	SOLID	BC	.040	1.76
A6124-7T	24	7/.0076	TC	.043	1.87
A6124-7	24	7/.0076	BC	.043	1.87
A6122-1T	22	SOLID	TC	.045	2.58
A6122-1	22	SOLID	BC	.045	2.58
A6122-7T	22	7/.0096	TC	.049	2.74
A6122-7	22	7/.0096	BC	.049	2.74
A6120-1T	20	SOLID	TC	.052	3.85
A6120-1	20	SOLID	BC	.052	3.85
A6120-7T	20	7/.0121	TC	.056	4.08
A6120-7	20	7/.0121	BC	.056	4.08
A6120-10T	20	10/30	TC	.060	4.09
A6120-10	20	10/30	BC	.060	4.09
A6118-1T	18	SOLID	TC	.060	5.83
A6118-1	18	SOLID	BC	.060	5.83
A6118-16T	18	16/30	TC	.067	6.14
A6118-16	18	16/30	BC	.067	6.14
A6118-19T	18	19/.0092	TC	.066	6.12
A6118-19	18	19/.0092	BC	.066	6.12
A6116-1T	16	SOLID	TC	.071	8.93
A6116-1	16	SOLID	BC	.071	8.93
A6116-19T	16	19/29	TC	.076	8.85
A6116-19	16	19/29	BC	.076	8.85
A6116-26T	16	26/30	TC	.080	9.59
A6116-26	16	26/30	BC	.080	9.59

PRODUCT DESCRIPTION

Tinned or bare copper wire, either stranded or solid, with semi-rigid PVC insulation.

CONSTRUCTION

Conductor: Tinned or Bare Copper, Solid or Stranded
 Insulation: Semi-rigid Polyvinyl Chloride
 Insulation Thickness: 0.010"

APPLICATIONS

Internal Wiring in Electric Bookkeeping, Accounting, Time-Recording Machines, or Electronic Equipment if within a chassis or protected from mechanical injury.

INDUSTRY LISTINGS & STANDARDS

UL Style 1061 (AWM 1061) 300V 80°C
 Temperature Range: -10°C to +80°C
 Voltage Rating: 300 Volts
 Passes UL VW-1 Flame Test

COLOR CHART

Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray, White (Stripping Available)

AVAILABLE PUT-UPS

Reels: 500, 1000, 2500, 5000, 10000 feet
 Drums, Half-Drums
 Custom Put-ups available upon request

CABLE IDENTIFICATION

ADC xx AWG (UL) AWM STYLE 1061 80C 300V VW-1 E178258B

