

**UL Style 3321**  
HOOK UP WIRE



**RoHS Compliant**

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including (UL) and CSA.

Part Number	AWG	Conductor		Nominal O.D. (inch)	Weight, Lbs. / 1000 ft.
		Strand	Type		
A32124-1T	24	SOLID	TC	0.080	3.44
A32124-1	24	SOLID	BC	0.080	3.44
A32124-7T	24	7/32	TC	0.084	3.77
A32124-7	24	7/32	BC	0.084	3.77
A32122-1T	22	SOLID	TC	0.085	4.40
A32122-1	22	SOLID	BC	0.085	4.40
A32122-7T	22	7/30	TC	0.090	4.87
A32122-7	22	7/30	BC	0.090	4.87
A32120-1T	20	SOLID	TC	0.092	5.84
A32120-1	20	SOLID	BC	0.092	5.84
A32120-10T	20	10/30	TC	0.096	6.10
A32120-10	20	10/30	BC	0.096	6.10
A32118-1T	18	SOLID	TC	0.100	8.04
A32118-1	18	SOLID	BC	0.100	8.04
A32118-16T	18	16/30	TC	0.106	8.30
A32118-16	18	16/30	BC	0.106	8.30
A32116-1T	16	SOLID	TC	0.111	11.42
A32116-1	16	SOLID	BC	0.111	11.42
A32116-26T	16	26/30	TC	0.119	12.16
A32116-26	16	26/30	BC	0.119	12.16
A32114-1T	14	SOLID	TC	0.124	16.64
A32114-1	14	SOLID	BC	0.124	16.64
A32114-41T	14	41/30	TC	0.134	17.59
A32114-41	14	41/30	BC	0.134	17.59
A32112-1T	12	SOLID	TC	0.141	24.74
A32112-1	12	SOLID	BC	0.141	24.74
A32112-65T	12	65/30	TC	0.153	26.04
A32112-65	12	65/30	BC	0.153	26.04
A32110-1T	10	SOLID	TC	0.162	37.39
A32110-1	10	SOLID	BC	0.162	37.39
A32110-105T	10	105/30	TC	0.178	39.68
A32110-105	10	105/30	BC	0.178	39.68

**PRODUCT DESCRIPTION**

Tinned or bare copper wire, either stranded or solid, with thermosetting, chemically cross-linked polyethylene.

**CONSTRUCTION**

Conductor: Tinned or Bare Copper, Solid or Stranded  
Insulation: Chemically Cross-Linked Polyethylene (XLPE)  
Insulation Thickness: 0.030"

**APPLICATIONS**

Internal wiring of appliances, transformers, electrical heating, motors, ballast, lighting and cooking equipment.

**INDUSTRY LISTINGS & STANDARDS**

UL Style 3321 Bare Copper  
Temperature Range: +150°C  
Voltage Rating: 600 Volts  
Other: CL 1503/AWM, RoHS

**COLOR CHART**

Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Grey, White

**AVAILABLE PUT-UPS**

Reels: 500, 1000, 2500, 5000, 10000 feet  
Drums, Half-Drums  
Custom Put-ups available upon request

**CABLE IDENTIFICATION**

ADC xx AWG RU AWM STYLE 3321 150C 600V  
E178258



The information contained on this specification is intended to be used as a guide in product selection and is believed to be reliable.

ADC has made every effort to ensure the data shown above is accurate at the time of publication. This specification is subject to change anytime without notice. Rev HU0618

**PHONE: (800) 343 2579 • FAX: (828) 389 3922 • WWW.ADCABLE.COM**