

PREMIUM AUDIO CABLE



SPECIALTY CABLES

AWG	COND	STRAND	PART NO.	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
				INCH	mm	INCH	mm	
18	2	41	32182	.025	.635	.184	4.67	23
	4	41	32184	.025	.635	.216	5.49	37
16	2	65	32162	.025	.635	.239	6.07	35
	4	65	32164	.025	.635	.279	7.09	60
14	2	105	32142	.025	.635	.271	6.88	49
	4	105	32144	.025	.635	.313	7.95	84
12	2	168	32122	.025	.635	.302	7.67	64
	4	168	32124	.025	.635	.357	9.07	121

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to www.adcable.com for the most up to date information. Rev 0419



CLARIFY™ brand cables are Advanced Digital Cable's proven solution for your high end audio needs. CLARIFY™ cables are first constructed using a premium grade copper which is 98% pure oxygen free for maximum conductivity and corrosion resistance. CLARIFY™ cables utilize a high strand conductor for maximum flexibility and true accurate signal transfer.

Advanced Digital Cable uses premium compounds for insulating and jacketing which provide low attenuation and maximum flexibility while remaining easy to pull and strip.

Every component in an audio system is critical and CLARIFY™ cables have been designed to reduce noise and CLARIFY™ the signal. Has your cable been built to deliver crystal clear audio? Are you getting the pure sound the components are producing? Get your audio signal clarified with the name and quality you trust. Get CLARIFY™ from Advanced Digital Cable.



(800) 343 2579 • www.adcable.com

PRODUCT DESCRIPTION

PVC insulated high strand count bare copper conductors, twisted with an overall high flex PVC jacket.

APPLICATIONS

- Intercom/PA Systems
- Home Theater Systems
- Sound/Audio Systems
- Stadium & Arena Speaker Systems

SPECIFICATIONS

Conductor High Strand Bare Copper

Insulation

- 18 AWG - .010"
- 16-12 AWG - .018"

Jacket .025" PVC

NEC Articles CL3R/725

Voltage Rating 300 V

Temp. Rating -25°C to 75°C

COLOR CODE CHART

Cond Color

- 1 Black
- 2 White
- 3 Red
- 4 Green

AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

XX AWG XC PREMIUM AUDIO CABLE (UL) TYPE CL3R E179334

*14-12 AWG are not recognized by c(UL) or c(ETL).