



AWG	COND	STRAND	PART NO.	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
				INCH	mm	INCH	mm	
22	2 1Pr Shld / 1Pr Unshld	7	912221SD	.018	.46	.148	3.76	22
	2 Each Pair Shielded	7	912222SD	.018	.46	.146	3.71	21
	3 Pair Overall Shielded	7	912233SD	.017	.43	.230	5.84	27
	3 Each Pair Shielded	7	912232SD	.017	.43	.180	4.57	30
	3 2 Pr Shld / 1 Pr Unshld	7	912231SD	.017	.43	.236	5.99	28
	4 2 Pr Shld / 2 Pr Unshld	7	912245SD	.017	.43	.260	6.60	33
20	2 2 Pr 1 Shielded	7	912021SD	.017	.43	.164	4.17	30
	3 3 Pr Overall Shld	7	912033SD	.017	.43	.196	4.98	37
	2 2 Pr Ind. Shld	7	912022SD	.017	.43	.164	4.17	30
	3 2 Pr Shld / 1 Pr Unshld	7	912032SD	.017	.43	.260	6.60	39
18	4 2 Pr Shld / 2 Pr Unshld	7	912042SD	.017	.43	.282	7.16	48
	2 1Pr Shld / 1Pr Unshld	7	911821SD	.014	.36	.170	4.32	36
	2 Each Pair Shielded	7	911822SD	.018	.46	.213	5.41	41
	3 Pair Overall Shielded	7	911823SD	.018	.46	.240	6.10	48
	3 Each Pair Shielded	7	911832SD	.015	.38	.237	6.02	55
	4 2 pr Shld / 2 pr Unshld	7	911842SD	.018	.46	.300	7.62	64

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to www.adcable.com for the most up to date information. Rev 0622

PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, short overall twist length, aluminum mylar shielding with drain wire and an overall low smoke white PVC jacket.*

APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

SPECIFICATIONS

Conductor Stranded Bare Copper
Insulation

- 22 AWG .007"
- 20 AWG .008"
- 18 AWG .009"

Shield Aluminum Mylar

Jacket Low Smoke PVC

NEC Articles

- FPLP/760, CMP/800, CL3P/725

Voltage Rating 300 V

Temp. Rating -5°C to 75°C

Drain Wire Size

- 24 AWG Tinned Copper

COLOR CODE CHART

Cond Color

- 1 Black/Red
- 2 Black/White
- 3 Black/Green
- 4 Black/Blue

AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

*14-12 AWG are not recognized by c(UL) or c(ETL).

*Other colors available upon request. Please consult factory for minimums and lead times.



(800) 343 2579 • www.adcable.com